



UKCA DoP 105

1	Laminate Flooring	EN 13329:2021
---	-------------------	---------------

2	Floor covering for internal use under dry conditions
---	--

3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim 4018427 03 08
---	--

4	System of assessment and verification of constancy of performance	3 ^{*)}
---	---	-----------------

Thickness	7 mm	8 mm	PS +2 mm	Silent +2 mm	Silent CT +2 mm
Key properties					
Reaction to fire ^{*)}	C _{fl} - s1				
Emission of formaldehyde ^{*)}	E1				
Emissions of VOC	≤ 0,062 mg/m³				
Content of dangerous substances	Compliant, not actively added				
Water resistance	NPD				
Slip resistance	μ ≥ 0,30				
Electrical behaviour	Antistatic				
Thermal conductivity [W/(m·K)]	0,121	0,123	+0,035	+0,200	+0,050
Durability as regards reaction to fire	NPD				

BS EN 14041:2004/AC:2006

The performance of the product identified in (1) is in conformity with the declared performance in (5).
This declaration of performance is issued under the sole responsibility of the manufacturer (3).

6 Signed for and on behalf of the manufacturer

*Peter Huber,
head of production*

Stephanskirchen, 20.06.2022

^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0321 SATRA, United Kingdom) has/have performed type testing according to the system specified in (4).