

Declaration of Performance
Construction Products (Amendment etc.)
(EU Exit) Regulations 2020 No. 1359

UKCA DoP 164

1	Wood floor covering		EN 14354: 2017
2	Floor covering for internal use under dry conditions		
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim		
4	System of assessment and verification of constancy of performance		3 ^{*)}
5	Thickness	9,9 mm	BS EN 14342:2013
	Mass density	> 800 kg/m ³	
	Key properties		
	Reaction to fire ^{*)}	C _{FI} - s1	
	Emission of formaldehyde ^{*)}	E1	
	Content of PCP	< 5 x 10 ⁻⁶ⁿ	
	Emission of other dangerous substances	NPD	
	Breaking strenght	NPD	
	Slip resistance	NPD	
	Thermal conductivity	≥ 0,148 W/(m·K)	
	Natural durability	Class 5 (EN 350-1)	
6	The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3). Signed for and on behalf of the manufacturer Peter Huber, head of production  Stephanskirchen, 17.01.2023		
^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0766 EPH Dresden, NB 2079 eco Institut) has/have performed type testing according to the system specified in (4).			

BS EN 14342:2013